

Welcome to IEEE Xplore®

Home Your search matched **151** of **969893** documents.

What Can I Access? A maximum of **151** results are displayed, **25** to a page, sorted by **Relevance** in **descending** order.

Log-out You may refine your search by editing the current search expression or entering a new one in the text box.

Tables of Contents

Journals & Magazines Then click **Search Again**.

interface and trap and frequency

Conference Proceedings

Standards

Search Again

Results:

Journal or Magazine = **JNL** Conference = **CNF** Standard = **STD**

1 Low-frequency measurements and modeling of MLC capacitors

Zhang, T.; Yoo, I.K.; Burton, L.C.; Components, Hybrids, and Manufacturing Technology, IEEE Transactions on [see also IEEE Trans. on Components, Packaging, and Manufacturing Technology, Part A, B, C] , Volume: 12 Issue: 4 , Dec. 1989

Page(s): 613 -618

Print Format

[\[Abstract\]](#) [\[PDF Full-Text \(356 KB\)\]](#) **IEEE JNL**

2 Low-frequency measurements and modelling of MLC capacitors

Zhang, T.; Yoo, I.K.; Burton, L.C.; Electronic Components Conference, 1989. Proceedings., 39th , 22-24 May 1989

Page(s): 206 -211

[\[Abstract\]](#) [\[PDF Full-Text \(332 KB\)\]](#) **IEEE CNF**

3 Observation and characterization of near-interface oxide traps with C-V techniques

Cohen, N.L.; Paulsen, R.E.; White, M.H.; Electron Devices, IEEE Transactions on , Volume: 42 Issue: 11 , Nov. 1995

Page(s): 2004 -2009

[\[Abstract\]](#) [\[PDF Full-Text \(568 KB\)\]](#) **IEEE JNL**

4 The dynamic conductance and transconductance in double-gate (gate-all-round) SOI devices

Welcome to IEEE Xplore®

- Home
- What Can I Access?
- Log-out

Tables of Contents

- Journals & Magazines
- Conference Proceedings
- Standards

Search

- By Author
- Basic
- Advanced

Member Services

- Join IEEE
- Establish IEEE Web Account
- Access the IEEE Member Digital Library

 Print FormatYour search matched **9** of **969893** documents.A maximum of **9** results are displayed, **25** to a page, sorted by **Relevance** in **descending** order.

You may refine your search by editing the current search expression or entering a new one in the text box.

Then click **Search Again**.

Interface and trap and thin and oxide

Search Again**Results:**Journal or Magazine = **JNL** Conference = **CNF** Standard = **STD****1 L-band dielectric resonator filters and oscillators with low vibration sensitivity and ultra low noise***Sparagna, S.M.;*

Frequency Control, 1989., Proceedings of the 43rd Annual Symposium on , 31 May-2 June 1989

Page(s): 94 -106

[\[Abstract\]](#) [\[PDF Full-Text \(740 KB\)\]](#) **IEEE CNF****2 Ultra low noise high gain W-band InP-based HEMT downconverter***Chow, P.D.; Tan, K.; Streit, D.; Garske, D.; Liu, P.; Yen, H.C.;*
Microwave Symposium Digest, 1991., IEEE MTT-S International , 10-14 June 1991
Page(s): 1041 -1044 vol.3[\[Abstract\]](#) [\[PDF Full-Text \(252 KB\)\]](#) **IEEE CNF****3 Effects of microcontaminants in oxygen during gate oxide growth: interfacial effects and device reliability***Beck, S.E.; George, M.A.; Bohling, D.A.; Shemanski, B.J.; McGuire, J.T.; Hames, G.A.; Wortman, J.J.; Lanford, W.A.;*
Advanced Semiconductor Manufacturing Conference and Workshop. 1994. ASMC 94 Proceedings. IEEE/SEMI , 14-16 Nov. 1994
Page(s): 100 -106[\[Abstract\]](#) [\[PDF Full-Text \(608 KB\)\]](#) **IEEE CNF****4 Initial results from the deployment of an ultra-wide band scatterometer***Reed, R.; Long, D.G.; Arnold, D.V.; Collyer, R.S.;*

WEST Search History

DATE: Tuesday, September 09, 2003

<u>Set Name</u>	<u>Query</u>	<u>Hit Count</u>	<u>Set Name</u>
side by side		result set	

DB=USPT; PLUR=YES; OP=OR

L4	(L2 or L3) and (interface adj (trap\$1 or states))	63	L4
L3	((324/765 324/71.1 324/71.5)!.CCLS.)	2744	L3
L2	((438/14 438/17 438/18)!.CCLS.)	1553	L2
L1	(interface adj traps).ti. or (interface adj traps).ab.	28	L1

END OF SEARCH HISTORY

WEST Search History

DATE: Wednesday, September 10, 2003

<u>Set Name</u>	<u>Query</u>	<u>Hit Count</u>	<u>Set Name</u>
			result set
side by side	<i>DB=USPT,PGPB,JPAB,EPAB,DWPI,TDBD; PLUR=YES; OP=OR</i>		
L1	oxide and (semiconductor or silicon) and (interface adj (state or trap)) and (frequency or rate) and gate and drain and source	818	L1

END OF SEARCH HISTORY